



Outdoor Freestanding

Allure Series

Premium freestanding kiosk designed for flagship locations.



Optional: PCAP touch



Sensor board



Remote monitoring



Anti-vandal protected glass



Aluminum side protectors



Patented air cooling system



Auto brightness control



IP66 weatherproof enclosure

Panel	Screen Size (diagonal)	75" x 2
	Active Display Area (inch mm)	64.95 x 36.5331649.664 x 927.936
	Resolution	3840 x 2160
	Aspect Ratio	16:09
	Display Colors	1.07B
	Brightness (cd/m2; typ.)	3,000
	Contrast Ratio	1200 : 1
	Response Time (ms; GTG)	8
	Viewing Angle	178°/178°
	Lifetime (hours)	50,000
	Backlight type	LED
Input	2x [1xVGA 3xHDMI 1xPC audio 1xRS232C 1x IR 1xUSB(Media Player)]	
Media Player (USB)	Movie	MPEG-2 MPEG-4
	Photo	JPEG PNG BMP
	Music	MP3
Power	Operating Voltage	100 - 240 VAC
	Consumption (typ.)	1.5KW (750W x 2)
	Consumption per nits (max)	0.5W (0.25W x 2)
Mounting (Bottom mounting)	M10 wedge anchor (10 pcs)	
Features	Auto Cooling System	Yes
	Anti-Vandal Glass	8mm
	Anti Reflection Coating	Yes
	Auto Brightness Sensor	Yes
Weight	Set (lb kg)	780.44 354
Operation	Temperature (°C)	-30-50
	Humidity (%)	20-80
	Storage (°C)	-40 - 60
	OSD Language	12 Lang
Approvals	Ingress Protection	IP66
Dimension	Set (W x H x D), inch mm	49.40 x 88.77 x 14.96 1255 x 2255 x 380

Specifications and design are subject to change without notice.

